



## Technical Bulletin

## Furex ABC Spezial

## **Product description**

Main component:	%	ammonium dihydrogen ph	osphate	21,5	± 1,5
Standard colour:		cream, other colors available on request			
Apparent density:	g/100 ml	87 ± 7			
Particle size: < 40 μm < 63 μm > 125 μm	ca. %	56 75 9	±8 ±8 ±5		
Fluidity:	g/sek.	65 – 85			
Temperature stability:	°C	(-30) – (+60)			
Moisture content:	%	≤ 0,25			
Water repellency:	All raw materials are carefully selected and of the highest quality. With the addition of high-quality silicone oil, Furex ABC Spezial is protected against moisture and temperature fluctuations in a wide range of applications and is highly hydrophobic.				
Physiological safety declaration:	In case of fire there are no toxicological concerns about the handling and using of the a.m. powder				
Durability:	If stored properly, the extinguishing capacity will not decrease even after several years (at least 5 years). The storage may cause clumping, which can be loosened again by moving the powder.				
Foam compatibility:	Furex ABC Spezial is compatible with all common extinguishing foams.				
Manufacturer's note:	Mixing different types of powder (ABC and BC) can lead to clumping and gas formation, which can increase the pressure in the fire extinguisher to a dangerous level.  Furex ABC Spezial corresponds to the current European standard EN 615.				

Technical alteration reserved. This edition cancels all previous data sheets.