

<b>Technical Bulletin</b>	<b>Furex AFFF 20</b>
---------------------------	----------------------

### Product description

<b>Description:</b>	Water film-forming foam
<b>Rating ratio:</b>	II B (3%, tapwater), II A (3%, seawater)
<b>Standard colour:</b>	yellowish
<b>Sediment content:</b>	none
<b>Density at 20 °C:</b>	approx. 1.01 g/cm <sup>3</sup>
<b>pH-value:</b>	approx. 8.5
<b>Freezing temperature:</b>	approx. -7°C
<b>Recommended storage temperature:</b>	10 °C – 30 °C
<b>Application:</b>	Water film-forming heavy foam agent for use on non-polar liquids
<b>Durability:</b>	6 years, with proper handling and storage in original closed packing.
<b>Manufacturer's note:</b>	<p>The foam agent is suitable for combined use with foam-compatible fire extinguishing powder. Mixing different foaming agents and extinguishing agent additives can lead to crystallization, flocculation or corrosion. In this case, the manufacturer does not guarantee the extinguishing ability of the extinguishing agent.</p> <p>Furex AFFF 20 is certificated according to the current European Norms EN 1568 and EN 3.</p>

Technical alteration reserved. This edition cancels all previous data sheets.